

SELF PROPELLED SCISSOR LIFTS From 7m-18 m working height



SCISSORS are used where less reach and height but more workspace and lifting capacity is required. They are designed to provide larger platform work areas and generally to allow for heavier loads than boom lifts. Scissors lifts may be maneuvered in a manner similar to boom lifts, but the platform may be raised only vertically, except for an available option that extends the deck horizontally. Scissor lifts are available in various models with maximum platform heights of up to 50ft. Battery powered scissor are available for indoor applications and diesel powered scissor are applicable for tough ground condition and long distance travel.

Model	GS 5390	GS4390	4069LE	GS3268	GS3246	GS2646	GS2046	MX19
Working height	18.15m	15.10m	14.19m	11.58m	11.75m	10.00m	8.10m	7.80m
Platform height	16.15 m	13.10m	12.19m	9.75m	9.75m	8.00m	6.10m	5.80m
Platform size	3.89x1.83m	3.98x1.83m	2.92x1.65m	2.5x1.55m	1.14x2.13m	2.21x1.17m	2.26x1.15m	1.64x0.74m
Platform size - extended	6.57x1.83m	7.38x1.83m	3.83x1.65m	4.04x1.55m	1.14x3.04m	3.29x1.17m	3.18x1.15m	2.63x0.74m
SWL / Lift capacity	680kg	680kg	360kg	454kg	315kg	454kg	544kg	227kg
Power Option	Diesel	Diesel	Electric	Electric/Diesel	Electric	Electric	Electric	Electric
Closed height	3.15m	2.93m	2.83m	2.46m	2.40m	2.28m	2.13m	2.10m
Closed width	2.29m	2.29m	1.75m	1.73m	1.17m	1.17m	1.17m	0.76m
Closed length	5.40m	3.98m	3.1m	2.67mm	2.44m	2.44m	2.41m	1.83m
Weight	7,632kg	7,323kg	5,300kg	3,670kg (D) 3,633kg (E)	2,800kg	2,167kg	1,974kg	1,306kg
Drive Option/Tires	4 x 4 / RT	4 x 4 / RT		RT	NM	NM	NM	NM

